



ELECTRIC CARGO VAN

		VEHICLE TYPE		GXA5032XXY	/BEV				
		NUMBER OF SEATS (DRIVER INCLUIDED) 2-5							
		NUMBER OF DOC	DRS		5		RARED VOLTAG	GE (V)	336
DIMENSION		WHEELBASE (mm) TREAD (mm)		4490*1610*1900			BATTERY TYPE	LFP LITHIUM	IRON PHOSPHATE
				3	050	BATTERY	SLOW CHARGI	NG TIME (H)	6
				1386/1408			FAST CHARGIN	IG TIME (H)	1
				2622*1457*1	1340		BATTERY CAPA	CITY (KWH)	41.86
WEIGHT		TOTAL WEIGHT (Kg) CURB WEIGHT (Kg)		2	2510		RADAR (OPTIONA	L)	REAR
				1430			PARKING VIDE	O SYSTEM (OPTIONAL)	REVERSING
						SAFETY SYSTEM	STABILITY		ESP/DSC/ESC
PASS PARAMETER	ΛFTFR	MINIMUN GROUND CLEARANCE (mm) MINIMUN TUMING RADIUS (m)		mm)	125		ABS BRAKE SYS	ABS BRAKE SYSTEM FRONT DISC BRAKE	
	ILILIN				11.9				HYDRAULIC BRAKE
		OD 4 D 4 DII IT (10()					SAFETY BRAKE	SYSTEM	EBD / CBC
		GRADABILITY (%)			20				
DRIVING RANGE		WORKING CONDITION METHOD (m) 250					SUSPENSION FRONT MCPHERSON INDEPENDENT		
								REAR LEAF SPI	RING SUSPENSION
RANGE		RANGE (Km) NED	C		285		TIDE EDOLIT		175 /750140
OTEEDINIO		T /DE	EDO DA OK AN	D DIV II O V I (EDO)			TIRE FRONT		175/75R14C
STEERING		TYPE EPS RACK AND PINION (EPS) (AII)			(AII)		TIRE REAR		185R14C
		DEATED TODOLIE	(N L N A)	00.7	220		AID CONDITION	VIED (STEEL)	A A A A II I A I
MOTOR		REATED TORQUE (N.M) REATED POWER (KW) MOTOR TYPE CHARGE TYPE		90 /		MODE	AIR CONDITION		MANUAL
					/ 60 ASAA	MORE	DIGITAL CONN		USB
					ΛSM Y CC		POWER WINDO	7003	ALL
			תאסר	TZ100VCIA					

TZ180XSIN101

EVSG



ENGINE MOTOR TYPE

TRANSMISSION TYPE

